

Partially Stainless Steel Linear Actuated Elevating Cart 19-1/2 In. x 32 In. 500 Lb. Capacity Blue/Silver

MODEL CART-500-LA-PSS

Ergonomic Solutions / Linear Actuated Elevating Carts

PRODUCT OVERVIEW

The linear actuated elevating cart transports materials from workstation to workstation with ease. The platform is raised and lowered with an electric linear actuator for precise positioning. Linear actuator will not allow platform to drift down- a common problem with hydraulic carts. This linear actuated cart is powered with a DC battery and features an on-board charger. A hand held pendant control connects to power unit with a coil cord. The units rolls smoothly on two rigid and two swivel casters. The platform, handle, base frame, caster brackets, and hardware are stainless steel. The scissor legs are zinc-plated. Battery pack, charger, and hand control are plastic. The linear actuator is plastic with a chrome-plated piston, while the wheels are...

KEY FEATURES

- Unique lift design quickly raises & lowers material
- Ergonomic cart design improves user safety
- Caster construction provides easy portability when loaded
- Steel construction offers long lasting rugged use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
185 lbs

ASSEMBLED SIZE
44.5" W x 53.5" L x 42" H

SHIP WEIGHT
186 lbs

PACKAGE 1 SIZE
42" W x 49" D x 45" H

COLOR / FINISH
Silver

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	500
Platform Width (in.)	19-1/2
Platform Length (in.)	32
Lowered Height (in.)	15
Raised Height (in.)	33
Battery Quantity/Voltage	(2) 12V
Caster Diameter (in.)	4
Caster Width (in.)	2
Caster (qty.)	4
Caster Material	Poly-on-Steel
Coil Cord Length (ft.)	6
Overall Length (in.)	53-1/2
Overall Width (in.)	44-1/2
Overall Height (in.)	42
Battery Depth	7
Battery Width	4
Battery Height	9
Battery Weight	12
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=277>