

# Steel Alternating Crossover Ladder 10 Step 56 Degrees 88 In. x 81 In. 350 Lb. Capacity Yellow

**MODEL COLA-3-56-20**

Industrial Ladders / Alternating Step Cross-Over Ladders

## PRODUCT OVERVIEW

Mount this alternating step cross-over ladder where you need permanent access at crossover points. Alternating step design for shorter overall span than other units. The upper platform features removable two sided high handrail with mid-rail and fixed toe boards to prevent objects from rolling off. Includes lag-down points for securing to floor.

## KEY FEATURES

- Alternating step design offers shorter overall span than other units
- Pre-drilled lag-down points make installation quick and easy
- Two-sided hand railing provides ladder user safety
- Meets OSHA rule 1910.25(f) et seq

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**282 lbs**

**ASSEMBLED SIZE**  
**24.0625" W x 88" L x 80.25" H**

**SHIP WEIGHT**  
**324 lbs**

**PACKAGE 1 SIZE**  
**30" W x 88" D x 22" H**

**COLOR / FINISH**  
**Yellow**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                   |
|--------------------------------------|-------------------|
| Uniform Capacity (lb.)               | 350               |
| Number of Steps on Each Side         | 5                 |
| Clearance Span Height (in.)          | 34-13/16          |
| Clearance Span Width (in.)           | 24-1/8            |
| Step Angle (degrees)                 | 56                |
| Platform Handrail Height (in.)       | 39                |
| Platform Mid-Rail (in.)              | 21                |
| Toeboard (in.)                       | 4                 |
| Usable Width between Handrails (in.) | 20-1/16           |
| Step Width (in.)                     | 9-1/8             |
| Step Depth (in.)                     | 10-1/2            |
| Base Width (in.)                     | 23-11/16          |
| Tread                                | Serrated          |
| OSHA                                 | 1910.25(f) et seq |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=615>