Steel Counter Balanced Drum Lifter Single Grip 62 In. Lifting Height 1,000 Lb. Capacity Yellow/Black

MODEL S-CB-62-SDC

Drum Handling Equipment / Counter-Balanced Drum Lifters (Powered Lift & Power Drive)

PRODUCT OVERVIEW

Ideal for confined areas, placing drums in cabinets, loading and unloading drums on/off pallets and scales. Transport 30 and 55 gallon steel, plastic, or fiber drums with ease. Two (2) 12V DC (lead acid batteries) drive and lift motor handles heavy-duty jobs. Ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/ lower controls, proprietary safety-enhancing emergency reverse function, and horn.

KEY FEATURES

- Emergency reverse belly switch instantly reverses direction
- Transport a variety of drum styles
- Simple controls for quick movement
- Ability to raise to high levels of workspace

CORE PRODUCT DATA

ASSEMBLED WEIGHT	ASSEMBLED SIZE	SHIP WEIGHT
1846 lbs	33" W x 76" L x 78" H	1936 lbs

PACKAGE 1 SIZE	COLOR / FINISH	FREIGHT TYPE
45" W x 87" D x 84" H	Yellow / Black	LTL Palletized

AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1,000
Style	Single Grip
Front Caster Wheel Diameter (in.)	6-1/4
Drive Wheel Diameter (in.)	10
Caster Wheel Type	Poly-on-Steel
Lifting Height Max (in.)	62
Lifting Height Min. (in.)	Zero
Works With (gal.)	(1) 30 or (1) 55
Drum Material	Steel, Plastic and Fiber
Fork Width (in.)	3-1/8
Fork Size (WxTxL)	3-1/8 x 1-3/16 x 30
Mast	Single
Overall Mast Height (in.)	78-1/4
Drive Motor (kw.)	0.7
Lift Motor (kw.)	2.0
Safety Shield	Yes
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703** Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?PID=793